



### Main

Aesthetic name	Unica
Aesthetic cover frame name	Unica Basic
Product or component type	2 socket-outlets
Device presentation	Complete socket outlet
Outlet poles configuration	2P + E
Outlet standard	German
Socket additional information	In pin pack Side earth
Rated current	16 A 250 V AC 50/60 Hz
Number of modules	2 modules
Fixing mode	Long claws
Cover plate colour tint	Ivory RAL 9010
Quantity per set	Set of 1 blister

### Complementary

Connections - terminals	Screw terminals
Cable cross section	≤ 4 mm <sup>2</sup> flexible cable ≤ 4 mm <sup>2</sup> rigid cable
Minimum load breaking capacity	100 operations 1.25 I <sub>n</sub> and 1.1 I <sub>un</sub> , cos φ = 0.6
Electrical durability	10000 cycles , cos φ = 0.8
Insulation resistance	≥ 5 MOhm /500 V
Material	ABS (acrylonitrile butadiene-styrene) for cover frame ASA + PC for mechanism cover PBT GF30 for fixing frame
Embedding depth	29.8 mm
Depth	39.7 mm
Width	85 mm
Height	80 mm

### Environment

Dielectric strength	≥ 2000 V
Standards	UNE 20315
Ambient air temperature for operation	15...30 °C
Ambient air temperature for storage	0...35 °C
IK degree of protection	IK01
IP degree of protection	IP40
Environmental characteristic	UV resistant Acetone Alcohol Ammonia Bleach Liquid soap Oil Petrol Window-cleaning fluid

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.