



Main

Aesthetic name	Unica
Product or component type	1 socket-outlet
Device presentation	Mechanism with zamak fixing frame
Outlet poles configuration	2P + E with shutters
Outlet standard	German
Socket additional information	Shuttered Side earth
Rated current	16 A 250 V AC 50/60 Hz
Number of modules	2 modules
Fixing mode	Screws
Cover plate colour tint	Ivory RAL 9010
Quantity per set	Set of 1 film

Complementary

Connections - terminals	Screw terminal
Cable cross section	≤ 4 mm ² flexible cable ≤ 4 mm ² rigid cable
Minimum load breaking capacity	100 operations 1.25 I _n and 1.1 U _n , cos φ = 0.6
Electrical durability	10000 cycles , cos φ = 0.8
Insulation resistance	≥ 5 MOhm /500 V
Material	Polyamide 6 for mechanism cover Zamak for fixing frame
Embedding depth	29.8 mm
Depth	39.7 mm
Width	70.9 mm
Height	70.9 mm
Product weight	0.0695 kg

Environment

Dielectric strength	≥ 2000 V
Standards	UNE 20315
Product certifications	FR.ME63.B02375
Ambient air temperature for operation	15...30 °C
Ambient air temperature for storage	0...35 °C
IK degree of protection	IK01
IP degree of protection	IP40
Environmental characteristic	UV resistant Acetone Alcohol Ammonia Bleach Liquid soap Oil Petrol Window-cleaning fluid