



### Main

|                               |   |
|-------------------------------|---|
| Aesthetic name                | Unica   |
| Product or component type     | Rocker switch   |
| Device presentation           | Mechanism with zamak fixing frame                                     |
| Switch application            | Switch  |
| Switch additional information | Blue neon lamp connected internally<br>With internal power connection |
| Rated current                 | 10 AX 250 V AC 50/60 Hz   |
| Number of modules             | 2 modules   |
| Fixing mode                   | By 4 screws   |
| Cover plate colour tint       | White RAL 9003  |

### Complementary

|                                |   |
|--------------------------------|---|
| Switch function                | 1-way   |
| Opening distance               | > 3 mm  |
| Actuator                       | Rocker  |
| Pilot light                    | Neon locator lamp , colour : blue , current consumption : 1 mA , temperature rise : 15 °C |
| Connections - terminals        | Screwless terminals   |
| Cable cross section            | ≤ 2.5 mm <sup>2</sup> rigid cable<br>≤ 4 mm <sup>2</sup> flexible cable                   |
| Minimum load breaking capacity | 200 operations 1.25 In and 1.1 Un , cos φ = 0.3   |
| Electrical durability          | 10000 cycles  |
| Insulation resistance          | ≥ 5 MOhm /500 V   |
| Material                       | Zamak for fixing frame  |
| Embedding depth                | 21.7 mm   |
| Depth                          | 33.8 mm   |
| Width                          | 70.9 mm   |
| Height                         | 70.9 mm   |
| Product weight                 | 0.0572 kg   |

### Environment

|                                       |  |
|---------------------------------------|--|
| Dielectric strength                   | ≥ 2000 V   |
| Standards                             | EMC directive<br>EN 60669-1<br>LV directive  |
| Product certifications                | FR.ME63.B02736   |
| Ambient air temperature for operation | 25...35 °C   |
| Ambient air temperature for storage   | 0...50 °C  |
| IK degree of protection               | IK01   |
| IP degree of protection               | IP40   |
| Environmental characteristic          | UV resistant<br>Acetone<br>Alcohol<br>Ammonia<br>Bleach<br>Liquid soap<br>Oil<br>Petrol<br>Window-cleaning fluid |
| Environmental health and issues       | Halogen free   |