



Main

Aesthetic name	Unica
Product or component type	Rocker switch
Device presentation	Mechanism with zamak fixing frame
Switch application	Switch
Switch additional information	With internal power connection
Rated current	10 AX 250 V AC 50/60 Hz
Number of modules	2 modules
Fixing mode	By 4 screws
Cover plate colour tint	White RAL 9003

Complementary

Switch function	1-way
Opening distance	> 3 mm
Actuator	Rocker
Connections - terminals	Screwless terminals
Cable cross section	≤ 2.5 mm ² flexible cable ≤ 2.5 mm ² rigid cable
Minimum load breaking capacity	200 operations 1.25 In and 1.1 Un , cos φ = 0.3
Electrical durability	10000 cycles
Insulation resistance	≥ 5 MOhm /500 V
Material	Zamak for fixing frame
Embedding depth	21.7 mm
Depth	33.8 mm
Width	70.9 mm
Height	70.9 mm
Product weight	0.0593 kg

Environment

Dielectric strength	≥ 2000 V
Standards	EMC directive EN 60669-1 LV directive
Product certifications	FR.ME63.B02736
Ambient air temperature for operation	25...35 °C
Ambient air temperature for storage	0...50 °C
IK degree of protection	IK01
IP degree of protection	IP40
Environmental characteristic	UV resistant Acetone Alcohol Ammonia Bleach Liquid soap Oil Petrol Window-cleaning fluid
Environmental health and issues	Halogen free