



## Main

Aesthetic name	Unica
Product or component type	Rocker switch
Device presentation	Mechanism with zamak fixing frame
Switch application	Switch
Switch additional information	With internal power connection
Rated current	10 AX 250 V AC 50/60 Hz
Number of modules	2 modules
Fixing mode	By 4 screws
Cover plate colour tint	White RAL 9003

## Complementary

Switch function	Intermediate
Opening distance	> 3 mm
Actuator	Rocker
Connections - terminals	Screwless terminals
Cable cross section	≤ 2.5 mm <sup>2</sup> rigid cable ≤ 4 mm <sup>2</sup> flexible cable
Minimum load breaking capacity	200 operations 1.25 In and 1.1 Un , cos φ = 0.3
Electrical durability	10000 cycles
Insulation resistance	≥ 5 MOhm /500 V
Material	Zamak for fixing frame
Embedding depth	21.7 mm
Depth	33.8 mm
Width	70.9 mm
Height	70.9 mm
Product weight	0.0603 kg

## Environment

Dielectric strength	≥ 2000 V
Standards	EMC directive EN 60669-1 LV directive
Product certifications	FR.ME63.B02736
Ambient air temperature for operation	25...35 °C
Ambient air temperature for storage	0...50 °C
IK degree of protection	IK01
IP degree of protection	IP40
Environmental characteristic	UV resistant Acetone Alcohol Ammonia Bleach Liquid soap Oil Petrol Window-cleaning fluid
Environmental health and issues	Halogen free

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.