



Main

| | |
|-------------------------------|-----------------------------------|
| Aesthetic name | Unica |
| Product or component type | Rocker switch |
| Device presentation | Mechanism with zamak fixing frame |
| Switch application | Switch |
| Switch additional information | With internal power connection |
| Rated current | 10 AX 250 V AC 50/60 Hz |
| Number of modules | 2 modules |
| Fixing mode | By 4 screws |
| Cover plate colour tint | Ivory RAL 9010 |

Complementary

| | |
|--------------------------------|--|
| Switch function | Intermediate |
| Opening distance | > 3 mm |
| Actuator | Rocker |
| Connections - terminals | Screwless terminals |
| Cable cross section | ≤ 2.5 mm ² rigid cable ≤ 4 mm ² flexible cable |
| Minimum load breaking capacity | 200 operations 1.25 I _n and 1.1 I _{un} , cos φ = 0.3 |
| Electrical durability | 10000 cycles |
| Insulation resistance | ≥ 5 MOhm /500 V |
| Material | Zamak for fixing frame |
| Embedding depth | 21.7 mm |
| Depth | 33.8 mm |
| Width | 70.9 mm |
| Height | 70.9 mm |
| Product weight | 0.0603 kg |

Environment

| | |
|---------------------------------------|--|
| Dielectric strength | ≥ 2000 V |
| Standards | EMC directive EN 60669-1 LV directive |
| Product certifications | FR.ME63.B02736 |
| Ambient air temperature for operation | 25...35 °C |
| Ambient air temperature for storage | 0...50 °C |
| IK degree of protection | IK01 |
| IP degree of protection | IP40 |
| Environmental characteristic | UV resistant Acetone Alcohol Ammonia Bleach Liquid soap Oil Petrol Window-cleaning fluid |
| Environmental health and issues | Halogen free |

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.