



Main

Aesthetic name	Unica
Product or component type	Cord pushbutton switch
Device presentation	Mechanism
Switch application	Switch
Switch additional information	Cable length: 1m
Fixing mode	By 4 screws
Cover plate colour tint	Ivory RAL 9010
Material	ASA + PC for mechanism cover Zamak for fixing frame

Complementary

Switch function	Cord pushbutton
Rated current	10 A 250 V AC 50/60 Hz
Load current	10 A
Opening distance	> 3 mm
Actuator	Cord pushbutton
Number of modules	2 modules
Connections - terminals	Screwless terminals
Cable cross section	≤ 2.5 mm ² flexible cable ≤ 2.5 mm ² rigid cable
Minimum load breaking capacity	200 operations 1.25 I _n and 1.1 I _{un} , cos φ = 0.3
Electrical durability	40000 cycles , cos φ = 0.6
Insulation resistance	≥ 5 MOhm /500 V
Embedding depth	22.28 mm
Depth	42.08 mm
Width	70.9 mm
Height	70.9 mm
Product weight	0.0636 kg

Environment

Dielectric strength	≥ 2000 V
Standards	EMC directive EN 60669-1 LV directive
Product certifications	FR.ME63.B02736
Ambient air temperature for operation	25...35 °C
Ambient air temperature for storage	0...50 °C
IK degree of protection	IK01
IP degree of protection	IP40
Environmental characteristic	UV resistant Acetone Alcohol Ammonia Bleach Liquid soap Oil Petrol Window-cleaning fluid
Environmental health and issues	Halogen free