



Main

Aesthetic name	Unica
Product or component type	Key card switch
Device presentation	Mechanism with zamak fixing frame
Number of modules	2 modules
Fixing mode	Screws or claws
Additional information	With locator lamp
Cover plate colour tint	Ivory RAL 9010

Complementary

Load type	Fluorescent load with a corrected power factor control through appropriate relay
Rated current	10 A
[Ue] rated operational voltage	230 V +/- 10 % AC 50 Hz
Actuator	Card 54 x 86 x 0.85 mm (maximum)
Marking	Vertical insertion pictogram
Connections - terminals	Screw
Number of cables	2 ≤ 2.5 mm ² flexible 2 ≤ 2.5 mm ² rigid
Fuse type	Electronic
Maximum number of switchings	50000 operations
Material	ASA + PC for mechanism cover Zamak for fixing frame
Embedding depth	13.7 mm
Depth	34.5 mm for Unica Allegro cover frame 34.5 mm for Unica Plus cover frame 36 mm for Unica Basic cover frame 36 mm for Unica Colors cover frame
Width	70.9 mm
Height	70.9 mm
Product weight	0.0645 kg

Environment

Standards	EN 61058-1 RoHS compliant
Product certifications	FR ME63 B02736
Ambient air temperature for operation	5...30 °C
Ambient air temperature for storage	-20...60 °C
IK degree of protection	IK01
IP degree of protection	IP20
Environmental characteristic	UV resistant Acetone Alcohol Ammonia Bleach Liquid soap Oil Petrol Window-cleaning fluid