



Main

Aesthetic name	Unica Plus
Product or component type	Cover frame
Number of modules	4 modules
Number of gangs	2 gangs horizontal
Cover frame colour tint	Ivory RAL 9010
Decoration colour	Ivory RAL 9010

Complementary

Fixing mode	Clip-in
Material	ASA + PC for intermediate part ASA + PC for decorative frame ASA + PC for cover frame
Width	80 mm
Height	161 mm
Depth	13.5 mm
Distance between centers	71 mm
Product weight	0.035 kg

Environment

Standards	EN 60669-1 RoHS compliant UNE 20315
IK degree of protection	IK01
IP degree of protection	IP40
Environmental characteristic	UV resistant Acetone Alcohol Ammonia Bleach Liquid soap Oil Petrol Window-cleaning fluid
RoHS EUR conformity date	0610
RoHS EUR status	Compliant

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.