



Main

Aesthetic name	Unica
Product or component type	1 socket-outlet
Device presentation	Mechanism
Outlet poles configuration	2P + E
Outlet standard	German
Socket additional information	With earth (TTL) + security cover
Rated current	16 A 250 V AC 50/60 Hz
Number of modules	2 modules
Fixing mode	Clip-in
Cover plate colour tint	Ivory RAL 9010
Cover frame colour tint	Ivory RAL 9010
Quantity per set	Set of 1 box

Complementary

Connections - terminals	Screw terminal
Cable cross section	≤ 4 mm ² flexible cable ≤ 4 mm ² rigid cable
Minimum load breaking capacity	100 operations 1.25 I _n and 1.1 I _{un} , cos φ = 0.6
Electrical durability	10000 cycles , cos φ = 0.8
Insulation resistance	≥ 5 MOhm /500 V
Material	ASA + PC for cover frame ASA + PC for fixing frame Polyamide 6 for mechanism cover
Embedding depth	26.7 mm
Depth	36.7 mm
Width	90 mm
Height	80 mm
Product weight	0.088 kg

Environment

Dielectric strength	≥ 2000 V
Standards	UNE 20315
Product certifications	FR.ME63.B02375
Ambient air temperature for operation	15...30 °C
Ambient air temperature for storage	0...35 °C
IK degree of protection	IK01
IP degree of protection	IP44
Environmental characteristic	UV resistant Acetone Alcohol Ammonia Bleach Liquid soap Oil Petrol Window-cleaning fluid

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.