

Kima GG10


Application:

Thin floor construction in wet and dry areas.

Ordinary concrete constructions in wet and dry rooms.

Specification:

- Flameretardent, twin conductor with no electromagnetic fields.
- Steel armoured metallic sheath with minimum electric fields.
- Insulation class I
- IP67
- Operating temperature max +70°C.
- Mechanical strength, armoured class C according to EN60800.
- Voltage 230 Volt.
- Wattage 10 W/m.
- 2 m coldtail with metallic sheath.
- Manufactured according to EN60800, SS4242411.
- Complies with RoHS directive 2002/95/EC.



- 100 W/m² = c/c 10 cm
- 75 W/m² = c/c 13,5 cm
- 67 W/m² = c/c 15 cm
- 50 W/m² = c/c 20 cm
- 40 W/m² = c/c 25 cm

Part no.	EAN no.	Product Type	Length (m)	Wattage (W)	Tolerance total (Ohm)
E 89 877 01	7331002902348	KIMA GG10	13	130	387 - 448
E 89 877 02	7331002902355	KIMA GG10	22	220	228 - 265
E 89 877 03	7331002902362	KIMA GG10	30	300	168 - 194
E 89 877 04	7331002902379	KIMA GG10	43	430	117 - 135
E 89 877 05	7331002902386	KIMA GG10	52	520	97 - 112
E 89 877 06	7331002902393	KIMA GG10	63	630	80 - 92
E 89 877 07	7331002902409	KIMA GG10	70	700	72 - 83
E 89 877 08	7331002902416	KIMA GG10	80	800	63 - 73
E 89 877 09	7331002902423	KIMA GG10	91	910	55 - 64
E 89 877 10	7331002902430	KIMA GG10	100	1000	50 - 58
E 89 877 12	7331002902447	KIMA GG10	117	1170	43 - 50
E 89 877 13	7331002902607	KIMA GG10	130	1300	39 - 45
E 89 877 14	7331002902454	KIMA GG10	142	1420	35 - 41
E 89 877 16	7331002902614	KIMA GG10	160	1600	31 - 36
E 89 877 18	7331002902461	KIMA GG10	182	1820	28 - 32