

Kima Warm Floor Mat Kit



Application:

Thin floor construction on top of an existing concrete floor construction in wet and dry areas. Ordinary concrete constructions in wet and dry areas.

Important! The heating cable can not be cut.

Product content:

- Underfloor Heatingmat
- Thermostat, E 85 811 37
- Floor sensor tube

Specification:

- Kima Warm Floor Mat 120.
- Kima Zone 30.



Part no.	EAN no.	Product Type	Width (mm)	Length (m)	Wattage (W)	Area (m ²)	Tolerance total (Ohm)
E 89 877 38	7331002904120	KIMA WFMK 120	200	5,0	110	0,95	457 - 529
E 89 877 21	7331002904137	KIMA WFMK 120	200	8,0	190	1,6	265 - 306
E 89 877 22	7331002904144	KIMA WFMK 120	200	10,0	240	2,0	209 - 242
E 89 877 39	7331002904151	KIMA WFMK 120	200	12,0	285	2,4	176 - 204
E 89 877 23	7331002904168	KIMA WFMK 120	200	15,5	390	3,1	129 - 149
E 89 878 47	7331002905141	KIMA WFMK 120	500	1,9	110	0,95	457 - 529
E 89 878 51	7331002905158	KIMA WFMK 120	500	3,2	190	1,6	265 - 306
E 89 878 52	7331002905165	KIMA WFMK 120	500	4,0	240	2,0	209 - 242
E 89 878 48	7331002905172	KIMA WFMK 120	500	4,8	285	2,4	176 - 204
E 89 878 53	7331002905189	KIMA WFMK 120	500	6,2	390	3,1	129 - 149
E 89 878 49	7331002905196	KIMA WFMK 120	500	7,2	430	3,6	117 - 135
E 89 878 54	7331002905202	KIMA WFMK 120	500	8,0	470	4,0	107 - 124
E 89 878 55	7331002905219	KIMA WFMK 120	500	10,2	635	5,1	79 - 92
E 89 878 56	7331002905226	KIMA WFMK 120	500	12,6	760	6,3	66 - 77
E 89 878 57	7331002905233	KIMA WFMK 120	500	14,8	880	7,4	57 - 66
E 89 878 58	7331002905240	KIMA WFMK 120	500	17,0	975	8,5	52 - 60
E 89 878 60	7331002905257	KIMA WFMK 120	500	21,0	1300	10,5	39 - 45
E 89 878 63	7331002905264	KIMA WFMK 120	500	26,0	1550	13,0	32 - 38