

## Valena™ automatic switches, dimmers



7700 89 + 7744 51

7700 74 + 7744 61

Mechanisms supplied with cover plates, to be equipped with plates (p. 692)  
Screw or claw mounting

## Valena™ roller blinds control, master switches for hotel rooms and thermostats



7743 04 + 7700 11

7741 35 + 7743 51

7741 26 + 7743 51

Mechanisms supplied with cover plates, to be equipped with plates (p. 692)  
Screw or claw mounting

Pack	Cat.Nos	Automatic switches with movement detector
		230 V~ - 50/60 Hz Luminosity threshold: 3 to 1000 lux
		<b>Standard</b> 60-300 W for incandescent and halogen lamps 230 V~ Temporization: 6 seconds to 6 min. Can replace a switch without additional wiring Detection angle: 130°
1	7741 28	<ul style="list-style-type: none"> <li>● Ivory</li> <li>○ White</li> <li>● Brilliant Aluminium</li> </ul>
1	7742 28	
1	7702 28	
		<b>With override, with neutral</b> 1000 W for incandescent and halogen lamps 230 V~ 500 VA ELV lamps with electronic or ferromagnetic transformers, fluorescent tubes and compact lamps 100 VA fans Temporization: 1 second to 16 min Detection angle: 180° Can be remotely controlled via non-illuminated push-button
1	7741 89	<ul style="list-style-type: none"> <li>● Ivory</li> <li>○ White</li> <li>● Brilliant Aluminium</li> </ul>
1	7700 89	
1	7702 89	

Pack	Cat.Nos	Roller blinds control 10 A - 250 V~
		Automatic terminals
		<b>Switch with mechanical interlock</b>
1	7743 04	<ul style="list-style-type: none"> <li>● Ivory</li> <li>○ White</li> <li>● Brilliant Aluminium</li> </ul>
1	7744 04	
1	7701 04	
		<b>Push-button with electrical interlock</b>
1	7743 14	<ul style="list-style-type: none"> <li>● Ivory</li> <li>○ White</li> <li>● Brilliant Aluminium</li> </ul>
1	7744 14	
1	7701 14	
		<b>Roller blinds control for RTS somfy.</b> Allows the remote control of RTS Somfy roller blinds (lithium battery 3 V type CR 2032 supplied)
1	7741 79	<ul style="list-style-type: none"> <li>● Ivory</li> <li>○ White</li> <li>● Brilliant Aluminium</li> </ul>
1	7700 79	
1	7702 79	

Pack	Cat.Nos	Dimmers 230 V~ - 50 Hz
		<b>Rotary dimmer</b> Push for On/Off function Rotate for light level adjustment 100-1000 W for incandescent and halogen lamps 230 V~ 1000 VA ELV lamps with ferromagnetic transformers
1	7741 60	<ul style="list-style-type: none"> <li>● Ivory</li> <li>○ White</li> <li>● Brilliant Aluminium</li> </ul>
1	7700 60	
1	7702 60	
		<b>Rotary adjustment and control</b> 40-400 W for incandescent and halogen lamps 230 V~ 40-400 VA ELV lamps with ferromagnetic transformers
1	7741 61	<ul style="list-style-type: none"> <li>● Ivory</li> <li>○ White</li> <li>● Brilliant Aluminium</li> </ul>
1	7700 61	
1	7702 61	
		<b>Push-button dimmer - 40-400 W</b> With an On/Off button and a separate + / - button for dimming 40-400 W for incandescent and halogen lamps 230 V~ 40-400 VA ELV halogen lamps with electronic and ferromagnetic transformers Can be remotely controlled via non-illuminated push-button or two-way switch
1	7741 62	<ul style="list-style-type: none"> <li>● Ivory</li> <li>○ White</li> <li>● Brilliant Aluminium</li> </ul>
1	7700 62	
1	7702 62	
		<b>Push-button dimmer - 40-600 W</b> With an On/Off button and a separate + / - button for dimming 40-600 W for incandescent and halogen lamps 230 V~ 40-600 VA ELV halogen lamps with ferromagnetic transformers
1	7741 74	<ul style="list-style-type: none"> <li>● Ivory</li> <li>○ White</li> <li>● Brilliant Aluminium</li> </ul>
1	7700 74	
1	7702 74	

Pack	Cat.Nos	Master switches for hotel rooms
		For energizing a circuit by inserting a card Example of use: hotel room power supply only when the guest is present 230 V~ - 50/60 Hz
		<b>Standard</b> Compatible with a smart card for hotel room max. width 54 mm
10	7741 34	<ul style="list-style-type: none"> <li>● Ivory</li> <li>○ White</li> <li>● Brilliant Aluminium</li> </ul>
10	7742 34	
10	7702 34	
		<b>With time delay</b> Compatible with a smart card for hotel room max. width 54 mm or a key fob Cat.No 898 06 (p. 531) Approx 30 sec. after card removal
1	7741 35	<ul style="list-style-type: none"> <li>● Ivory</li> <li>○ White</li> <li>● Brilliant Aluminium</li> </ul>
1	7742 35	
1	7702 35	
		<b>Thermostats</b>
		<b>Standard</b> NO/NC contact to control heating or air-conditioning
1	7741 26	<ul style="list-style-type: none"> <li>● Ivory</li> <li>○ White</li> <li>● Brilliant Aluminium</li> </ul>
1	7742 26	
1	7702 26	
		<b>Comfort with switch</b> Comfort/reduce, manual or automatic with auxiliary input 230 V~
1	7741 27	<ul style="list-style-type: none"> <li>● Ivory</li> <li>○ White</li> <li>● Brilliant Aluminium</li> </ul>
1	7742 27	
1	7702 27	
		<b>For floor heating system</b> Comfort mode reduced with auxiliary input 230 V~ Supplied with floor sensor, length 20 m
1	7741 91	<ul style="list-style-type: none"> <li>● Ivory</li> <li>○ White</li> <li>● Brilliant Aluminium</li> </ul>
1	7700 91	
1	7702 91	