



### Main

Aesthetic name	Unica
Product or component type	1 socket-outlet
Device presentation	Mechanism with zamak fixing frame
Outlet poles configuration	2P + E
Outlet standard	German
Socket additional information	Side earth
Rated current	16 A 250 V AC 50/60 Hz
Number of modules	2 modules
Fixing mode	Screws
Cover plate colour tint	White RAL 9003
Quantity per set	Set of 1 film

### Complementary

Connections - terminals	Screw terminal
Cable cross section	≤ 4 mm <sup>2</sup> flexible cable ≤ 4 mm <sup>2</sup> rigid cable
Minimum load breaking capacity	100 operations 1.25 I <sub>n</sub> and 1.1 U <sub>n</sub> , cos φ = 0.6
Electrical durability	10000 cycles , cos φ = 0.8
Insulation resistance	≥ 5 MOhm /500 V
Material	Polyamide 6 for mechanism cover Zamak for fixing frame
Embedding depth	29.8 mm
Depth	39.7 mm
Width	70.9 mm
Height	70.9 mm
Product weight	0.0695 kg

### Environment

Dielectric strength	≥ 2000 V
Standards	UNE 20315
Product certifications	FR.ME63.B02375
Ambient air temperature for operation	15...30 °C
Ambient air temperature for storage	0...35 °C
IK degree of protection	IK01
IP degree of protection	IP40
Environmental characteristic	UV resistant Acetone Alcohol Ammonia Bleach Liquid soap Oil Petrol Window-cleaning fluid

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.