



Main

Aesthetic name	Unica
Product or component type	Data socket
Device presentation	Mechanism with zamak fixing frame + long claws
Socket number	1
Cable shielding type	U/UTP
Data socket type	RJ45 8 contact(s) Cat. 5e ,transmission rate : <= 100 MHz
Fixing mode	Long claws
Provided equipment	Label holder Protective flap
Cover plate colour tint	Ivory RAL 9010
Product compatibility	LexCom

Complementary

Communication network type	ATM 155 Mbps Ethernet 1000BASE-T
Organization of wire	Unshielded twisted pair
Number of modules	2 modules
Connections - terminals	Click
Material	ASA + PC for mechanism cover Zamak for fixing frame
Embedding depth	24.6 mm
Depth	35.8 mm
Width	70.9 mm
Height	70.9 mm
Product weight	0.055 kg

Environment

Standards	ISO 8877
Ambient air temperature for operation	15...30 °C
Ambient air temperature for storage	0...35 °C
IK degree of protection	IK01
IP degree of protection	IP40
Environmental characteristic	UV resistant Acetone Alcohol Ammonia Bleach Liquid soap Oil Petrol Window-cleaning fluid

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.